

1 In view of the remarks above, it is submitted that Claims 18, 20-23, 24-27, 32-35
2 as amended, and new Claim 36, should now all be in order for allowance. Therefore, early
3 notice of allowance of the aforementioned claims, and prompt advancement of this application
4 to issuance are earnestly solicited.

5 Since the total number of claims in this application is now 14 including 3
6 independent claims, no excess claims fees are due.

7 Respectfully submitted,

8 *William L. Chapin*

9 William L. Chapin, Reg. #27,317
10 16791 Sea Witch Lane
11 Huntington Beach, California 92649
12 Telephone: (714) 625-3570
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

AMENDMENTS TO THE CLAIMS

Claim 18 (Amended): An apparatus for attaching a protective cover to a corner of a frame, such as a picture frame, said frame having a pair of adjacent elongated frame channel members which intersect to form said corner, said protective cover being fabricated from a preform made of a thin sheet of flexible material, said apparatus comprising;

a. means for depositing a first quantity of adhesive on a surface of said first frame channel,

b. means for bending upwardly from [the] a plane of a base portion of said preform comprising a lower cover flap and located beneath said frame a first flap section adjacent to a side of said first frame channel member, said means comprising a first flap folder arm attached to a first end of a first vertically upwardly movable linear actuator, said arm being located in a first recess in an upper surface of a worktable, below said preform, whereby upward extensional motion of said first linear actuator forces said first flap section of said preform to bend upwardly from said worktable surface.

c. means for bending downwardly and inwardly towards said first frame channel member from the plane of said first flap section an end portion comprising a securement flap thereof to thereby overlie said first quantity of adhesive on said first frame channel member,

d. means for depositing a second quantity of adhesive onto an upper surface of said securement flap overlying said first quantity of adhesive,

e. means for bending upwardly from the plane of said base portion of said preform a second flap section adjacent a side of said second frame channel member.

f. means for bending downwardly and inwardly towards said second frame channel member an end portion of said second flap section comprising a second, upper cover flap to thereby overlie said second quantity of adhesive,

g. means for pressing said securement flap downwardly against said first quantity of adhesive to thereby adhere said securement flap to said first frame channel member, and

h. means for pressing said second, upper cover flap against said second quantity of adhesive to thereby adhere said upper cover flap to said securement flap.

Claim 20 (Amended): The apparatus of Claim [19] 18 wherein said means for bending [perpendicularly] downwardly and inwardly from said first side flap section of said preform a securement flap overlying said first frame channel member is further defined as being first rotary actuator means coupled to said first flap folder arm, said first rotary actuator means being effective in rotating said first flap folder arm from an elevated position vertically aligned with said first arm recess to a position overlying said first channel member, thereby bending over from said first flap section of said securement flap.

Claim 22 (Amended): The apparatus of Claim 21 wherein said means for bending said second upper cover flap [perpendicularly inwards] downwardly and inwardly from said [section] second flap section is further defined as being second rotary actuator means coupled to said second flap folder arm, said second rotary actuator means being effective in rotating said second flap folder arm from an elevated position vertically aligned with said second arm recess to a position overlying said second channel member.

Claim 24 (Amended): An apparatus for adhesively bonding a corner protector preform to a corner of a frame, such as a picture frame, said corner being defined by the intersection at a dihedral angle of first and second adjacent elongated intersecting channel members comprising two adjacent sides of said frame, said corner protector preform comprising a thin sheet of flexible material including

- (i) a vertically elongated, rectangularly-shaped inner spine flap having a width approximately equal to the thickness of said intersecting channel members,
- (ii) a first, lower face cover flap having a side coextensive with a first vertical side of said inner spine flap, and a base collinear with a laterally disposed base of said inner spine flap,
- (iii) a horizontally elongated, rectangularly-shaped outer spine flap, which depends downwardly from said base of said first, lower face cover flap having a height

1 approximately equal to the thickness of said intersecting channel members of said
2 frame,

3 (iv) a horizontally elongated securement flap depending downwardly from said outer
4 spine flap, and

5 (v) a second, upper face cover flap section shaped similarly to said lower face cover
6 flap section and joined to a second vertical side of said inner spine flap in a
7 laterally opposed location to said lower face cover flap, said apparatus comprising;

8 a. support means for supporting said preform and a corner of said frame overlying
9 said lower cover flap of said preform,

10 b. means for depositing a first quantity of adhesive onto a surface of said first frame
11 channel member,

12 c. means for bending upwardly and adjacent said first intersecting side channel
13 member of said frame from [the] a plane of said preform and said lower face cover flap, said
14 outer spine flap and said securement flap,

15 d. means for bending inwardly from said outer spine flap, said securement flap
16 [section] to a location overlying said first side channel member of said frame,

17 e. means for depositing a second quantity of adhesive onto an upper surface of said
18 securement flap overlying said first quantity of adhesive,

19 f. means for bending upwardly adjacent said second intersecting channel member
20 of said frame from the plane of said preform and said lower face cover flap said inner spine
21 flap and said upper face cover flap,

22 g. means for bending inwardly from said inner spine flap said upper face cover flap
23 to position a portion thereof [to] at a location overlying said quantity of adhesive on said
24 securement flap,

25 h. means for pressing said securement flap downwardly against said first quantity of
26 adhesive to thereby adhere said securement flap to said first frame channel member, and
27
28

1 i. means for pressing said second, upper cover flap against said second quantity of
2 adhesive to thereby adhere said upper cover flap to said securement flap, and

3 j. guide means for slidably receiving and holding said frame in a fixed horizontal
4 disposition relative to said support means, said guide means comprising in combination a
5 pair of elongated blocks disposed obliquely to one another and having inner facing obliquely
6 disposed wall surfaces inclined relative to one another at said dihedral angle of said frame,
7 said blocks having between converging longitudinal ends thereof a laterally disposed space
8 adapted to insertably receive said corner of said frame.

9 Claim 25 (Amended): The apparatus of Claim 24 wherein said means for releasably
10 securing said frame to said support[ing] means of said apparatus is further defined as being
11 a clamping bar.

12 Claim 26 (Amended): The apparatus of Claim 25 wherein said means for releasably
13 securing said frame to said support[ing] means of said apparatus is further defined as being
14 a clamping bar.

15 Claim 32 (Amended): The apparatus of Claim [31] 36 wherein said means for bending
16 said securement flap inwardly from said outer spine flap is further defined as first rotary
17 actuator means coupled to said first linear actuator means, said first rotary actuator means
18 being effective in rotating said inner wall of said first flap folder arm inwardly towards said first
19 frame channel member.

20 Claim 36 (New): An apparatus for adhesively bonding a corner protector preform to a
21 corner of a frame, such as a picture frame, said corner being defined by the intersection at
22 a dihedral angle of first and second adjacent elongated intersecting channel members
23 comprising two adjacent sides of said frame, said corner protector preform comprising a thin
24 sheet of flexible material including

25 (I) a vertically elongated, rectangularly-shaped inner spine flap having a width
26 approximately equal to the thickness of said intersecting channel members,
27
28

- 1 (ii) a first, lower face cover flap having a side coextensive with a first vertical side of
2 said inner spine flap, and a base collinear with a laterally disposed base of said
3 inner spine flap,
- 4 (iii) a horizontally elongated, rectangularly-shaped outer spine flap, which depends
5 downwardly from said base of said first, lower face cover flap and having a height
6 approximately equal to the thickness of said intersecting channel members of said
7 frame,
- 8 (iv) a horizontally elongated securement flap depending downwardly from said outer
9 spine flap, and
- 10 (v) a second, upper face cover flap section shaped similarly to said lower face cover
11 flap section and joined to a second vertical side of said inner spine flap in a
12 laterally opposed location to said lower face cover flap, said apparatus comprising;
- 13 a. support means for supporting said preform and a corner of said frame overlying
14 said lower cover flap of said preform, said support means having a generally flat, upper work
15 surface,
- 16 b. means for depositing a first quantity of adhesive onto a surface of said first frame
17 channel member,
- 18 c. means for bending upwardly and adjacent said first intersecting side channel
19 member of said frame from a plane of said preform and said lower face cover flap, said outer
20 spine flap and said securement flap, said means comprising in combination a first flap folder
21 arm having a flat wall surface disposed parallel to and spaced outwardly apart from said first
22 frame channel member, and first linear actuator means for elevating said first flap folder arm
23 vertically upwardly from a first recess in said upper work surface of said support means,
- 24 d. means for bending inwardly from said outer spine flap, said securement flap to a
25 location overlying said first side channel member of said frame,
- 26 e. means for depositing a second quantity of adhesive onto an upper surface of said
27 securement flap overlying said first quantity of adhesive,
- 28

1 f. means for bending upwardly adjacent said second intersecting channel member
2 of said frame from the plane of said preform and said lower face cover flap said inner spine
3 flap and said upper face cover flap,

4 g. means for bending inwardly from said inner spine flap said upper face cover flap
5 to position a portion thereof at a location overlying said quantity of adhesive on said
6 securement flap, means for pressing said securement flap downwardly against said first
7 quantity of adhesive to thereby adhere said securement flap to said first frame channel
8 member, and

9 h. means for pressing said second, upper cover flap against said second quantity of
10 adhesive to thereby adhere said upper cover flap to said securement flap.

CLEAN COPY OF AMENDED CLAIMS

Claim 18 (Amended): An apparatus for attaching a protective cover to a corner of a frame, such as a picture frame, said frame having a pair of adjacent elongated frame channel members which intersect to form said corner, said protective cover being fabricated from a preform made of a thin sheet of flexible material, said apparatus comprising;

a¹ i. means for depositing a first quantity of adhesive on a surface of said first frame channel,

j. means for bending upwardly from a plane of a base portion of said preform comprising a lower cover flap and located beneath said frame a first flap section adjacent to a side of said first frame channel member, said means comprising a first flap folder arm attached to a first end of a first vertically upwardly movable linear actuator, said arm being located in a first recess in an upper surface of a worktable, below said preform, whereby upward extensional motion of said first linear actuator forces said first flap section of said preform to bend upwardly from said worktable surface.

k. means for bending downwardly and inwardly towards said first frame channel member from the plane of said first flap section an end portion comprising a securement flap thereof to thereby overlies said first quantity of adhesive on said first frame channel member,

l. means for depositing a second quantity of adhesive onto an upper surface of said securement flap overlying said first quantity of adhesive,

m. means for bending upwardly from the plane of said base portion of said preform a second flap section adjacent a side of said second frame channel member.

n. means for bending downwardly and inwardly towards said second frame channel member an end portion of said second flap section comprising a second, upper cover flap to thereby overlies said second quantity of adhesive,

o. means for pressing said securement flap downwardly against said first quantity of adhesive to thereby adhere said securement flap to said first frame channel member, and

a¹
p.

means for pressing said second, upper cover flap against said second quantity of adhesive to thereby adhere said upper cover flap to said securement flap.

a² Claim 20 (Amended): The apparatus of Claim 18 wherein said means for bending downwardly and inwardly from said first side flap section of said preform a securement flap overlying said first frame channel member is further defined as being first rotary actuator means coupled to said first flap folder arm, said first rotary actuator means being effective in rotating said first flap folder arm from an elevated position vertically aligned with said first arm recess to a position overlying said first channel member, thereby bending over from said first flap section of said securement flap.

a³ Claim 22 (Amended): The apparatus of Claim 21 wherein said means for bending said second upper cover flap downwardly and inwardly from said second flap section is further defined as being second rotary actuator means coupled to said second flap folder arm, said second rotary actuator means being effective in rotating said second flap folder arm from an elevated position vertically aligned with said second arm recess to a position overlying said second channel member.

a⁴ Claim 24 (Amended): An apparatus for adhesively bonding a corner protector preform to a corner of a frame, such as a picture frame, said corner being defined by the intersection at a dihedral angle of first and second adjacent elongated intersecting channel members comprising two adjacent sides of said frame, said corner protector preform comprising a thin sheet of flexible material including

- (i) a vertically elongated, rectangularly-shaped inner spine flap having a width approximately equal to the thickness of said intersecting channel members,
- (ii) a first, lower face cover flap having a side coextensive with a first vertical side of said inner spine flap, and a base collinear with a laterally disposed base of said inner spine flap,
- (iii) a horizontally elongated, rectangularly-shaped outer spine flap, which depends downwardly from said base of said first, lower face cover flap having a height

1 approximately equal to the thickness of said intersecting channel members of said
2 frame,
3 (iv) a horizontally elongated securement flap depending downwardly from said outer
4 spine flap, and
5 (v) a second, upper face cover flap section shaped similarly to said lower face cover
6 flap section and joined to a second vertical side of said inner spine flap in a
7 laterally opposed location to said lower face cover flap, said apparatus comprising;
8 a. support means for supporting said preform and a corner of said frame overlying
9 said lower cover flap of said preform,
10 b. means for depositing a first quantity of adhesive onto a surface of said first frame
11 channel member,
12 c. means for bending upwardly and adjacent said first intersecting side channel
13 member of said frame from a plane of said preform and said lower face cover flap, said outer
14 spine flap and said securement flap,
15 d. means for bending inwardly from said outer spine flap, said securement flap to a
16 location overlying said first side channel member of said frame,
17 e. means for depositing a second quantity of adhesive onto an upper surface of said
18 securement flap overlying said first quantity of adhesive,
19 f. means for bending upwardly adjacent said second intersecting channel member
20 of said frame from the plane of said preform and said lower face cover flap said inner spine
21 flap and said upper face cover flap,
22 g. means for bending inwardly from said inner spine flap said upper face cover flap
23 to position a portion thereof at a location overlying said quantity of adhesive on said
24 securement flap, means for pressing said securement flap downwardly against said first
25 quantity of adhesive to thereby adhere said securement flap to said first frame channel
26 member, and
27
28

1 h. means for pressing said second, upper cover flap against said second quantity of
2 adhesive to thereby adhere said upper cover flap to said securement flap, and

3 i. guide means for slidably receiving and holding said frame in a fixed horizontal
4 disposition relative to said support means, said guide means comprising in combination a
5 pair of elongated blocks disposed obliquely to one another and having inner facing obliquely
6 disposed wall surfaces inclined relative to one another at said dihedral angle of said frame,
7 said blocks having between converging longitudinal ends thereof a laterally disposed space
8 adapted to insertably receive said corner of said frame.

9 Claim 25 (Amended): The apparatus of Claim 24 wherein said means for releasably
10 securing said frame to said support means of said apparatus is further defined as being a
11 clamping bar.

12 Claim 26 (Amended): The apparatus of Claim 25 wherein said means for releasably
13 securing said frame to said support means of said apparatus is further defined as being a
14 clamping bar.

15 Claim 32 (Amended): The apparatus of Claim 36 wherein said means for
16 bending said securement flap inwardly from said outer spine flap is further defined as first
17 rotary actuator means coupled to said first linear actuator means, said first rotary actuator
18 means being effective in rotating said inner wall of said first flap folder arm inwardly towards
said first frame channel member.

19 Claim 36 (New): An apparatus for adhesively bonding a corner protector preform to a
20 corner of a frame, such as a picture frame, said corner being defined by the intersection at
21 a dihedral angle of first and second adjacent elongated intersecting channel members
22 comprising two adjacent sides of said frame, said corner protector preform comprising a thin
23 sheet of flexible material including

24 (I) a vertically elongated, rectangularly-shaped inner spine flap having a width
25 approximately equal to the thickness of said intersecting channel members,
26
27
28

- a b
- (ii) a first, lower face cover flap having a side coextensive with a first vertical side of said inner spine flap, and a base collinear with a laterally disposed base of said inner spine flap,
 - (iii) a horizontally elongated, rectangularly-shaped outer spine flap, which depends downwardly from said base of said first, lower face cover flap and having a height approximately equal to the thickness of said intersecting channel members of said frame,
 - (iv) a horizontally elongated securement flap depending downwardly from said outer spine flap, and
 - (v) a second, upper face cover flap section shaped similarly to said lower face cover flap section and joined to a second vertical side of said inner spine flap in a laterally opposed location to said lower face cover flap, said apparatus comprising;
 - a. support means for supporting said preform and a corner of said frame overlying said lower cover flap of said preform, said support means having a generally flat, upper work surface,
 - b. means for depositing a first quantity of adhesive onto a surface of said first frame channel member,
 - c. means for bending upwardly and adjacent said first intersecting side channel member of said frame from a plane of said preform and said lower face cover flap, said outer spine flap and said securement flap, said means comprising in combination a first flap folder arm having a flat wall surface disposed parallel to and spaced outwardly apart from said first frame channel member, and first linear actuator means for elevating said first flap folder arm vertically upwardly from a first recess in said upper work surface of said support means,
 - d. means for bending inwardly from said outer spine flap, said securement flap to a location overlying said first side channel member of said frame,
 - e. means for depositing a second quantity of adhesive onto an upper surface of said securement flap overlying said first quantity of adhesive,

1 f. means for bending upwardly adjacent said second intersecting channel member
2 of said frame from the plane of said preform and said lower face cover flap said inner spine
3 flap and said upper face cover flap,

4 g. means for bending inwardly from said inner spine flap said upper face cover flap
5 to position a portion thereof at a location overlying said quantity of adhesive on said
6 securement flap,

7 h. means for pressing said securement flap downwardly against said first quantity of
8 adhesive to thereby adhere said securement flap to said first frame channel member, and

9 i. means for pressing said second, upper cover flap against said second quantity of
10 adhesive to thereby adhere said upper cover flap to said securement flap.



EXPRESS MAIL CERTIFICATE

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Article Number

EL730241463US

in an envelope addressed to:

Commissioner for Patents
P. O. Box 1450
Alexandria, Virginia 22313-1450

on: June 27, 2003

by: William L. Chapin

William L. Chapin

Signature

June 27, 2003

Date of Signature

RECEIVED
JUL 03 2003
TC 1700

AMENDMENT TO THE SPECIFICATION

METHOD AND APPARATUS FOR ADHESIVELY BONDING CORNER PROTECTORS ONTO PICTURE FRAMES AND THE LIKE BACKGROUND OF THE INVENTION

A. Field of the Invention

The present invention relates to methods and apparatus for protecting the corners of rectangularly-shaped frames such as picture frames, from impact damage during shipping. More particularly, the invention relates to a method and apparatus for adhesively bonding corner protectors onto the corners of a picture frame.

B. Description of Background Art

Picture frames for holding and displaying paintings, photographs, diplomas, certificates and similar flat articles are manufactured in prodigious quantities worldwide. Although picture frames vary in shape and construction details, most frames have a rectangular plan view shape. Moreover, the structure of most picture frames consists essentially of four elongated, straight channel members or moldings, each having formed therein an inner longitudinally disposed channel that intersects channels of adjacent members at ninety degree angles. Four such channel members fastened together form a rectangular ring-shaped frame. The channels or recesses in the moldings face inwardly of the frame, and comprise spaces for receiving a rectangularly-shaped flat display piece such as a photograph or painting, and sometimes, a backing panel, mat and protective cover glass.

Picture frames of the type described above are made from a variety of materials including, wood, metal and plastic. Whatever material the frame is made of, the geometry of a rectangular picture frame dictates that it have four peripheral members or moldings of generally uniform thickness transverse cross section which are joined to each other at forty-five degree miter angles to form ninety-degree corners. Since the sides of each molding intersect at an acute angle, i.e., 45 degrees, the frame corners as well as the molding corners are sharp, and are therefore highly subject to breakage, denting or cosmetic damage during shipment. Accordingly, most picture frames, whether empty or occupied, are fitted with some sort of

1 corner protectors during shipment. Such corner protectors are usually made of a relatively
2 inexpensive
3 recyclable material such as cardboard or polystyrene foam. Typical corner protectors of this
4 type are disclosed in U.S. Pat. Nos. 3,955,677, 4,598,825, and 5,447,233. Other patents,
5 related to protecting corners of objects during shipping include U.S. Pat. No. 4,407,898. Also,
6 U.S. Pat. No. 5,255,458 discloses a three-dimensional picture corner and U.S. Pat. No.
7 4,787,553 discloses a corner fastening device.

8 In addition to the above-referenced patents related to corner protectors and the
9 like, a variety of machines for bending sheet metal or cardboard of the type used for corner
10 projectors have been disclosed in the following U.S. Pat. Nos: 4,132,102, 4,585,432,
11 4,713,957, 4,857,038, 4,956,961, and 5,184,998.

12 None of the aforementioned references disclose a machine for automatically
13 attaching corner protectors to picture frames. Accordingly, the task of attaching corner
14 protectors to picture frames was formerly labor intensive and time consuming. In response to
15 those limitations of the prior art, the present inventor disclosed an automatic Method and
16 Apparatus For Attaching Corner Protectors to Picture Frames, in U.S. Patent No. 6,018,934.
17 In that patent, the present inventor disclosed a method and apparatus for installing covers to
18 protect picture frame corners from damage during shipment, utilizing thin cardboard preforms
19 having symmetric, left and right-hand, right-triangular cover flaps joined at vertical sides thereof
20 to opposite vertical sides of a vertically elongated, rectangular spine flap, the left-hand
21 triangular cover flap having depending downwardly from its base a horizontally elongated
22 rectangular side cover flap, and depending downwardly from the lower lateral edge of the side
23 cover flap a trapezoidally-shaped securement flap. The preform is positioned below a picture
24 frame corner, with intersecting side members of the frame vertically aligned with the sides of
25 the left-hand right-triangular cover flap, which serves as a lower face cover flap. The
26 apparatus includes folder mechanisms including flap folder arms which are retractable into
27 recesses provided in a work table, and which are extendible and rotatable to thereby bend the
28 side cover flap and securement flap into a vertical position adjacent a first side of the frame

1 corner and perpendicularly inwardly to overlie the first frame member, bend the spine flap and
2 right-hand triangular cover flap into a vertical position adjacent the second frame member, and
3 bend the right-hand triangular flap perpendicularly inwards from the spine flap to overlie the
4 second and first frame members. An automatic staple gun then inserts a staple downwardly
5 through the right-triangular cover flap into the securement flap and left-hand frame member,
6 securing the corner protector in a folded disposition over the frame corner. The present
7 invention was conceived of to provide a method and apparatus for adhesively bonding corner
8 protectors on the corners of picture frames, the method and apparatus being suitable for use
9 with picture frames made of metal or plastic, as well as wood.

10 OBJECTS OF THE INVENTION

11 An object of the present invention is to provide a method for attaching protective
12 covers to the corners of a picture frame, using an adhesive bonding process.

13 Another object of the invention is to provide an apparatus for automatically
14 attaching protective covers to the corners of picture frames using adhesive bonds.

15 Another object of the invention is to provide a method and apparatus for
16 automatically attaching protective covers to the corners of picture frames, in which a cover is
17 bonded to the corner of a frame by an adhesive bond, not requiring penetration of the frame
18 by a fastener.

19 Another object of the invention is to provide a method and apparatus for
20 automatically attaching protective covers to corners of a picture frame in which adhesive is
21 applied to a surface of a frame molding, a protective cover is positioned over the cover, and
22 the cover pressed against the adhesive to bond the cover to the frame molding.

23 Another object of the invention is to provide an apparatus for depositing a
24 quantity of adhesive on a surface of a picture frame molding, folding a flat sheet of flexible
25 material over the corner of a picture frame, depositing a quantity of adhesive on a surface of
26 the sheet, securing the folds of the sheet together by pressing an upper portion of the folded
27 sheet against a lower portion having adhesive on its surface to form a protective cover, and
28

1 adhering the cover to the picture frame by pressing the cover against adhesive on the molding
2 surface.

3 Another object of the invention is to provide an apparatus for bending a
4 cardboard preform cut to a pre-determined shape over the corner of the picture frame,
5 securing the folded portions of the cardboard preform by compressing a liquid adhesive
6 therebetween and allowing the liquid adhesive to solidify, thereby forming a corner protector,
7 and securing the corner protector to a molding of the frame by compressing a liquid adhesive
8 between the molding and corner protector and allowing the liquid adhesive to solidify, thereby
9 adhesively bonding the corner protector to the frame.

10 Another object of the invention is to provide a picture frame corner protector
11 attaching apparatus which includes means for clamping and holding a corner of a picture
12 frame, positioning under the picture frame corner a preform sheet of flexible material, the
13 preform sheet having the shape of left and right, lower and upper right triangular-shaped cover
14 flaps joined at their inner vertical edges by a vertically elongated, rectangular-shaped inner
15 spine flap to form a shape approximating that of a truncated isosceles triangle, the preform
16 having a horizontally elongated, rectangularly-shaped outer spine flap depending downwardly
17 from the left triangular corner flap and shaped similarly to the inner spine flap, and having
18 depending downwardly therefrom a trapezoidally-shaped securement flap, means for spraying
19 a first quantity of adhesive onto the upper surface of a first frame molding overlying the lower
20 triangular-shaped cover flap, bending the outer spine flap vertically upwards into contact with
21 the outer lateral side of the first frame molding, bending the securement flap down into a
22 horizontal position in contact with the adhesive on the surface of the first frame molding,
23 bending the inner spine flap and upper triangular cover flap vertically upwards into contact with
24 the outer lateral surface of the second frame molding, spraying a second quantity of adhesive
25 onto the upper surface of the securement flap overlying the first quantity of adhesive and
26 bending the upper triangular cover flap into compressive contact with the second quantity of
27 adhesive, thereby securing the upper triangular cover flap to the securement flap to form a
28 completed cover protector, and pressing the first quantity of adhesive between the lower

1 surface of the securement flap and the upper surface of the first frame molding to thereby
2 secure the corner protector to the frame.

3 Various other objects and advantages of the present invention, and its most
4 novel features, will become apparent to those skilled in the art by perusing the accompanying
5 specification, drawings and claims.

6 It is to be understood that although the invention disclosed herein is fully capable
7 of achieving the objects and providing the advantages described, the characteristics of the
8 invention described herein are merely illustrative of the preferred embodiments. Accordingly,
9 I do not intend that the scope of my exclusive rights and privileges in the invention be limited
10 to details of the embodiments described. I do intend that equivalents, adaptations and
11 modifications of the invention reasonably inferable from the description contained herein be
12 included within the scope of the invention as defined by the appended claims.

13 SUMMARY OF THE INVENTION

14 Briefly stated the present invention comprehends a method and apparatus for
15 automatically and adhesively bonding protective covers made of a sheet of flexible material,
16 e.g., cardboard, stock to the corners of frames, particularly rectangularly-shaped frames of the
17 type used to hold pictures, documents and the like, the covers being intended to protect the
18 corners of the frame from damage during shipment.

19 A preferred embodiment of an automatic adhesive bonding method and
20 apparatus according to the present invention preferably utilizes corner protectors made from
21 thin, flat sheets of cardboard, each pre-cut, by die cutting, for example, into a generally
22 triangular shape which includes panel sections which are bent out from the plane of the sheet
23 to form cover flaps which are to be folded over and enclose a corner and adjacent portions of
24 the side channel members of a conventional rectangularly-shaped picture frame. Four such
25 corner protectors are used to cover the four corners of the frame.

26 In a preferred embodiment of the invention, the plan view shape of the upper,
27 larger portion of the corner protector preform includes two mirror symmetric, left and right,
28 right-triangularly-shaped, panel sections having collinear horizontal bases joined to opposite

1 vertical sides of a vertically elongated rectangular, inner, or right-hand spine panel section.
2 The left and right triangularly-shaped panel sections serve as lower and upper cover flaps,
3 while the inner spine panel section serves as a first, right-hand spine cover flap for a picture
4 frame corner, as will be described below. Thus shaped, the upper portion of the preform has
5 the appearance of an isosceles triangle whose vertex is horizontally truncated. The preform
6 preferably includes a lower portion that has a horizontally elongated, rectangularly shaped
7 outer, or left-hand spine flap panel section which depends downwardly from the base of one
8 of the right-triangle flap panels, the left one, for example, and has the same width as that
9 panel. A trapezoidally-shaped securement flap panel section depends downwardly from the
10 bottom edge of the outer spine flap panel, the securement flap panel having a lower edge wall
11 parallel to but shorter than that of the outer spine flap panel. In a preferred embodiment, the
12 horizontal width of the vertically elongated inner spine flap panel and the vertical height of the
13 horizontally elongated outer spine flap panel have a common value which is slightly greater
14 than the thickness of a picture frame which is to be protected, e.g., about 15/16 inch for a
15 frame thickness of $5/8$ 7/8 inch. Preferably, the vertical side walls of the vertical inner spine
16 flap panel and the horizontally disposed upper and lower edges of the outer spine flap panel
17 are scored to facilitate folding those respective flaps to contact adjacent perpendicular channel
18 members or moldings of a picture frame.

19 According to the method of the present invention, a preform, score lines up, is
20 positioned below a corner of a picture frame. The corner of the frame is oriented with respect
21 to a preform with a pair of perpendicularly intersecting adjacent molding side walls defining
22 the corner of the frame vertically aligned with the perpendicular sides of the left-hand, lower
23 right-triangular cover flap having the downwardly depending outer spine and securement flaps.
24 A first quantity of adhesive is then deposited on the upper surface of left-hand frame molding,
25 near its intersection with the right-hand frame molding. Preferably, the first quantity of
26 adhesive consists of one or more blobs of molten hot melt adhesive sprayed onto the upper
27 surface of the molding from one or more nozzles of a pressurized hot melt glue gun positioned
28 above the frame. The outer spine flap and securement flap are then folded vertically upwards

1 as a planar unit along the upper or inner score line defining the junction between the base of
2 the left, lower, right triangularly-shaped lower cover flap and the outer spine flap. Next, the
3 securement flap is folded downwardly and inwardly along the lower or outer score line towards
4 a horizontal position, and the securement flap is pressed down onto the semi-liquid glue blobs
5 on the upper surface of the frame member overlying the left, lower triangularly-shaped cover
6 flap. A second quantity of adhesive is then deposited on the upper surface of the securement
7 flap by the glue gun. Then, the second, right-hand, right-triangularly-shaped upper cover flap
8 and inner spine flap are bent upwards as a unit along the innermost vertical fold line, i.e., the
9 left-hand vertical edge of the inner spine flap, to a vertical position. The right-hand, upper
10 triangular cover flap is then bent downwardly and laterally along the outermost, right-hand
11 vertical fold line of the inner spine flap to a horizontal position overlying the securement flap
12 and pressed down against the second quantity of adhesive on the upper surface of the
13 securement flap, thus securing the overlying, upper right-hand triangular cover flap to the
14 securement flap.

15 The apparatus according to the present invention includes a base plate or work
16 table having a flat upper surface for supporting a corner of a picture frame, and a frame holder
17 clamping jig for receiving and holding the corner of the picture frame on the surface of the
18 table.

19 Mounted on the table is a corner protector installation mechanism which includes
20 a pair of corner protector flap folder actuators positioned on opposite sides of the corner of a
21 picture frame held in the clamping jig. Each corner folder actuator includes a flat,
22 rectangularly-shaped flap-contacting arm mounted near a longitudinal end thereof on the upper
23 end of a post which is actuable by a linear actuator from a lower inactive position in which the
24 arm resides within a rectangularly-shaped recess in the upper surface of the base plate, with
25 the upper surface of the arm flush with the upper surface of the base plate, to an upper, active
26 position. Each post also includes a 90-degree rotary actuator means, which is effective in
27 rotating a flap contacting arm, when raised, from an outer position contacting the outer
28

1 vertically disposed side of a flap to an inner position effective in exerting an inwardly and
2 downwardly directed folding force on the flap.

3 In operation, the first, e.g., left corner folder actuator arm is extended vertically,
4 folding the outer spine flap and securement flap upwardly into a vertical position adjacent one
5 side of a frame. An automatic hot melt adhesive gun applicator head having nozzles
6 pressurized by air then deposits sprays a first quantity of hot melt adhesive onto the upper
7 surface of the frame molding adjacent to the first folder actuator arm. The arm is then rotated
8 inwards, bending the securement flap inwardly and downwardly into contact with the first
9 quantity of semi-liquid adhesive on the upper surface of the first frame molding strip, thus
10 bonding adhering the securement flap to the frame.

11 Next, the actuator arm of the second, e.g., right corner folder actuator is elevated,
12 folding the upper triangular corner protector flap upwardly to a position vertically adjacent the
13 outer edge of the second frame molding strip. The arm of the first, left corner folder actuator
14 is then rotated outwardly from its position overlying and holding down the securement flap. A
15 second quantity of molten hot melt adhesive is then sprayed onto the upper surface of the
16 securement flap. The arm of the second actuator is then rotated inwardly, bending the upper,
17 right-hand triangular cover flap down into contact with the securement flap. This action
18 presses the upper triangular cover flap down against the second quantity of adhesive on the
19 upper surface of the underlying securement flap, thereby securing adhering the flaps to each
20 other. The applicator head is then moved forcibly downwards by a pneumatic actuator, causing
21 a pair of fingers protruding downwardly from the head to press downwardly on the upper
22 surface of the upper triangular cover flap, causing secure adhesive bonds to be formed
23 between the securement flap and frame, and between the upper triangular cover flap and
24 securement flap. Both actuator arms are then automatically rotated and retracted to their
25 recessed positions, flush with the work table surface. At the same time, the frame holding
26 clamp is also automatically released, allowing the frame with attached corner protector to be
27 removed from the clamp.

1 The apparatus according to the present invention may optionally include means
2 for automatically and substantially simultaneously initiating operation of a pair of corner
3 protector installation mechanisms of the type described above, each time two adjacent corners
4 of a picture frame are fully inserted into and correctly oriented with respect to clamping jigs of
5 the mechanisms. In a preferred embodiment, apparatus components for implementing this
6 automatic operation include a pair of guide plates in each clamping jig that have inner vertically
7 disposed wall surfaces that define therebetween a ninety degree intersection angle or vertex,
8 which is cut off or truncated by a plane oriented at forty-five degrees to the guide bars, to
9 thereby form an opening for insertably receiving the corner of picture frame, with the
10 intersecting channel moldings of the frame aligned with the guide plates.

11 Each guide plate is provided, near the opening between the inner longitudinal
12 ends of the guide plate, with a sensor which provides an electrical signal indicating that a
13 frame corner molding has been fully inserted into the clamping jig. The electrical signals from
14 each pair of sensors for each of the two clamping jigs are logically ANDed, producing a
15 command signal to initiate automatic operation of the machine only when all three outer sides
16 of the frame channel moldings defining two adjacent corners of the frame are fully inserted into
17 and properly aligned with the guide plates of the two clamping jigs for proper operation of the
18 corner protector folding and attaching operation. This command signal initiates a sequence
19 of operations by which a pair of corner protectors are automatically attached in tandem to the
20 two corners of a picture frame. Upon completion of this automatic operation, the holding
21 clamps of both clamping jigs are automatically released, allowing the frame with a pair of
22 attached corner protectors installed to be withdrawn from engagement with the apparatus. The
23 frame may then be rotated one hundred and eighty degrees in a horizontal plane, and re-
24 inserted into the apparatus to initiate attachment of a pair of corner protectors to the remaining
25 two corners of the picture frame.

26 BRIEF DESCRIPTION OF THE DRAWINGS

27
28

1 Figure 1 is a front perspective view of an apparatus for adhesively bonding corner
2 protectors onto picture frames according to the present invention, showing a hot melt adhesive
3 machine comprising part of the apparatus.

4 Figure 2 is a fragmentary upper rear perspective view of the apparatus of Figure
5 1 on an enlarged scale, and showing guide rods and preforms used therewith removed to
6 show details of the apparatus.

7 Figure 3 is a front perspective view of an adhesive applicator head comprising
8 part of the apparatus of Figure 1.

9 Figure 4 is a front elevation view of the applicator head of Figure 3.

10 Figure 5 is a side elevation view of the applicator head of Figure 3.

11 Figure 6 is a lower plan view of the applicator head of Figure 3.

12 Figure 7 is an upper plan view of a corner protector preform or blank usable with
13 the apparatus of Figure 1.

14 Figure 8 is a rear perspective view of the apparatus of Figure 2 showing a supply
15 of corner protector preforms or blanks of the type shown in Figure 7 in a stack preparatory to
16 feeding individual preforms into a clamping position on the apparatus.

17 Figure 9 is a rear perspective view similar to that of Figure 8, but showing an
18 individual corner protector preform advanced to a clamping location, and showing a corner
19 protector in a stack from which the individual corner protector was advanced.

20 Figure 10 is a view similar to that of Figure 9, but showing a corner of a picture
21 frame inserted into a clamping jig comprising part of the apparatus, the picture frame corner
22 being positioned above the individual corner protector preform of Figure 9, and showing a
23 clamp bar of the clamping jig brought down into compressive contact with the upper surface
24 of the picture frame.

25 Figure 11 is a view similar to that of Figure 10, but showing streams of adhesive
26 issuing from the adhesive applicator head of Figures 3 through 6, the streams impinging on
27 the upper surface of a channel member of the picture frame to thereby deposit thereon a first
28 adhesive blob consisting of two glue dots.

1 Figure 12 is a view similar to that of Figures 10 and 11, but showing a first corner
2 flap actuator comprising part of the apparatus in an upwardly actuated position.

3 Figure 13 is a view of the apparatus of Figure 1 similar to that of Figure 12, but
4 showing a fold-effecting arm of the first corner flap actuator rotated to contact and fold down
5 a securement flap of the corner protector preform into a position overlaying the picture frame.

6 Figure 14 is a view similar to that of Figure 13, but showing streams of adhesive
7 issuing from the adhesive applicator head of Figures 2 through 6, the streams impinging on
8 the upper surface of the securement flap to thereby deposit thereon a second adhesive blob
9 consisting of two glue dots.

10 Figure 15 is a view of the apparatus similar to that of Figure 13, but showing a
11 second corner flap actuator of the apparatus in an upwardly actuated position.

12 Figure 16 is a view of the apparatus of Figure 1 similar to that of Figure 15, but
13 showing a fold-effecting arm of the second corner flap actuator rotated to contact and fold
14 down a triangularly-shaped upper cover flap of the corner protector preform into a position
15 overlying the securement flap of the corner protector preform.

16 Figure 17 is a view of the apparatus of Figure 1 similar to that of Figure 16, but
17 showing the fold-effecting arm of the first corner flap actuator rotated back into an inactive,
18 home position, and showing an adhesive applicator head comprising part of the apparatus
19 actuated downwardly to thereby press a flat lower portion of the head forward of nozzles
20 protruding downwardly from the head into compressive contact with the upper surface of that
21 portion of the second, triangularly-shaped upper cover flap overlying the securement flap of
22 the corner protector preform, thereby pressing the glue dots between the flaps together to
23 thereby adhere the flaps together and thereby pressing the lower surface of the securement
24 flap against the glue dots on the picture frame channel molding, thereby adhering the
25 securement flap to the picture frame.

26 Figure 18 is a fragmentary side elevation view of the apparatus of Figure 17,
27 showing the applicator head on an enlarged scale, but in a partially lowered position.

1 Figure 19 is a view similar to that of Figure 18, but showing the applicator head
2 in a fully lowered position, as shown in Figure 17, and showing certain structural elements
3 thereof removed for clarity.

4 DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Figures 1-19 depict a method and apparatus according to the present invention
6 for adhesively bonding corner protectors onto picture frames and the like. The structure and
7 function of certain portions of the apparatus according to the present invention are described
8 in detail in the present inventor's U.S. Patent No. 6,018,934, the entire specification, claims,
9 drawings, and abstract which are hereby incorporated by reference into the present
10 application.

11 Referring now to Figures 1 and 2, an apparatus 20 for adhesively bonding corner
12 protectors onto the corners of picture frames and the like may be seen to include a corner
13 protector installation mechanism 30. Mechanism 30 is similar in structure and function to the
14 apparatus disclosed in U.S. Patent No. 6,018,934. Notably, however, as will be described in
15 detail below, mechanism 30 according to the present invention utilizes an adhesive dispensing
16 gun rather than the staple gun disclosed in the '934 patent. Thus, corner protector installation
17 mechanism 30, in contrast to the apparatus disclosed in the '934 patent, can be used to install
18 corner protectors on frames, such as metal or plastic frames, ~~where it~~ which would not be
19 ~~feasible to damaged by staple stapling~~ the protector to the frame.

20 As shown in Figures 1 and 2, corner protector installation mechanism 30 includes
21 a generally rectangular box-shaped enclosure 31 surmounted by a generally flat, upper base
22 plate or work table 32. As may be seen best by referring to Figure 1, apparatus 30 includes
23 an elongated, generally straight frame holder/clamping jig 33 mounted on the upper surface
24 34 of work table 32. Preferably, clamping jig 33 is disposed obliquely, e.g., at 45 degrees, with
25 respect to the rectangular plan-view shape of work table 32. As shown in Figures 1, 8, 10 and
26 18, clamping jig 33 is spaced above upper surface 34 of table 32, and includes a longitudinally
27 elongated, horizontally disposed, generally rectangular-shaped upper straight beam member
28 35, supported at opposite transverse ends thereof by a pair of laterally opposed, left and right

1 guide plates 36L, 36R, respectively. Guide plates 36 have flat and parallel lower and upper
2 surfaces, 236 and 237, these surfaces supporting clamp beam member 35 so that its lower
3 surface 37 is parallel to and spaced above upper surface 34 of work table 32.

4 As shown in Figure 1, enclosure 31 of mechanism 30 has parallel, vertically
5 disposed left and right side panels 72 and 73, which are perpendicular to front and rear
6 vertically disposed panels 75, 74. Front panel 75 is preferably joined to left and right side
7 panels 72, 73 by left and right vertically disposed transition panels 28, 29. The latter are
8 obliquely angled to front panel 75, e.g., at 45 degrees. This construction enables pairs of
9 mechanisms 30 to be oriented with longitudinal axes of the mechanism, defined by a horizontal
10 line centered in work table 32 and perpendicular to front panel 75, perpendicular to one
11 another, with transition panels 29, 28 of mechanisms 20 spaced closely next to one another.
12 Thus arranged, pairs of mechanisms 30 may optionally be employed in tandem, in a manner
13 similar to that described in co-pending application Serial No. ~~09/687,358~~ 09/687,356, filed
14 10/13/00, now U.S. Patent No. 6,418,700, the entire disclosure of which is hereby incorporated
15 by reference into this present application.

16 As shown in Figures 1 and 18, left and right guide plates 36L and 36R have inner
17 longitudinally disposed vertical wall surfaces 238L and 238R, respectively. If extended
18 inwardly or rearwardly towards the center of work table 32, inner vertical surfaces 238L and
19 238R of guide plates 36L and 36R would intersect to form a right angle corner. However, as
20 shown in Figures 1, 2, and 18, inner ends of guide plates 36L and 36R are truncated by an
21 obliquely disposed cutting plane which forms obliquely disposed inner vertical transverse face
22 walls 239L and 239R, respectively, that are coplanar with the cutting plane, and angled at 45
23 degrees to inner vertical side walls 238L and 238R. Thus arranged, inner vertical side walls
24 238L and 238R form guide surfaces along which may be slid the outer side walls of side
25 channel members or moldings of a rectangular picture frame that intersect each other at a
26 ninety-degree corner. A laterally disposed space 240 between opposed inner corners 241L
27 and 241R of guide plates 36L and 36R allows the corner of a picture frame to protrude
28 inwardly beyond inner face walls 239L and 239R of the guide plates.

1 As may be seen best by referring to Figures 1, 8, 10, and 18, clamping jig 33
2 includes a horizontally disposed, elongated straight clamp bar 38 located below and in vertical
3 alignment with clamp beam member 35. Clamp bar 38 is vertically movably held with respect
4 to clamp beam member 35. Thus, as shown in Figures 1, 8, and 18, clamping jig 33 includes
5 a linear actuator comprising a double acting pneumatic cylinder 40, for raising and lowering
6 clamp bar 38. Clamp bar cylinder 40 is mounted on the upper surface 41 of clamping jig
7 support beam 35, and has a piston rod 42 which protrudes vertically downwards through a
8 bore 43 provided through the thickness dimension of the support beam. The lower end of
9 piston rod 42 has a square transverse sectional shape which protrudes through a similarly
10 shaped bore through clamp bar 38, and is secured to the clamp bar by a screw 39. Since
11 pneumatic cylinder 40 is of the type in which piston rod 42 is non-rotatable, clamp bar 38 is
12 maintained in a fixed horizontal orientation when moved vertically with respect to work table
13 32.

14 As shown in Figures 2 and 18, clamp bar cylinder 40 has an upper pressurized
15 "down" air inlet port 44 connected to a first "down" air inlet hose 45, and a second, lower, "up"
16 air inlet port 46 connected to a second, "up" air inlet hose 47. Hoses 45 and 47 connect to
17 tubular fittings 48 and 49 which protrude downwards through upper surface 34 of work table
18 32, to control valves and a source of pressurized air, as will be discussed in detail below.
19 When pressurized air is supplied to "up" inlet port 46 of clamp air cylinder 40, pressurized air
20 on the lower side of a piston within the cylinder forces the piston, attached piston rod 42, and
21 attached clamp bar 38 upwards to an upper, unlocked position, as shown in Figure 1.
22 Conversely, when pressurized air is supplied to "down" inlet port 44 of clamp air cylinder 40,
23 pressurized air on the upper side of the piston within the cylinder forces the piston and clamp
24 bar 38 downwards to a lower position in clamping contact with a picture frame A, as shown in
25 Figure 10.

26 A preferred embodiment of mechanism 30 according to the present invention
27 includes a feeder mechanism 70 for automatically feeding a single corner protector preform
28 50 at a time to a pre-determined position beneath clamping bar 38 of clamping jig 33, prior to

1 inserting a frame to be protected into the clamping jig. The structure and function of feeder
2 mechanism 70 may be best understood by first reviewing the construction of corner protector
3 preforms 50 used with apparatus 30. Figure 7, shows a corner protector preform 50 of the
4 type the apparatus 30 is intended to be used with.

5 As shown in Figure 7, preform 50 is made of a thin sheet of readily bendable
6 material, such as corrugated cardboard. Preform 50 has two laterally mirror symmetric, left
7 and right triangularly-shaped panel sections bendable out the plane of the sheet to form lower
8 and upper triangular cover flaps 51 and 52, respectively. In the orientation of preform 50
9 shown in Figure 7, flap 51 is on the left-hand side of the figure, and will be referred to as the
10 left-hand flap as a matter of convenience throughout the ensuing discussion. Left and right,
11 lower and upper triangular cover flaps 51 and 52 have collinear horizontal bases 53 and 54
12 joined at their respective ninety degree corner angles to opposite vertical sides 55 and 56 of
13 a vertically elongated, rectangular panel section comprising ~~an~~ a first, inner spine flap 57,
14 which has a base 58 collinear with the bases of the triangles. Thus shaped, preform 50 has
15 an appearance approximating that of an isosceles triangle having a horizontal base 53-58-54
16 and an upper vertex truncated by a horizontal edge 59 parallel to the base.

17 Referring still to Figure 7, preform 50 may be seen to include a horizontally
18 elongated, rectangularly shaped panel section comprising ~~an~~ a second, outer spine flap 60
19 which depends downwardly from base 53 of left-hand triangular flap 51, and has the same
20 width as that flap. A trapezoidally-shaped securement flap 61 depends downwardly from the
21 bottom edge wall 62 of outer rectangular spine flap 60, the securement flap having an upper
22 edge wall coextensive with bottom edge wall 62 of the outer spine flap, and a lower edge wall
23 63 parallel to but shorter than edge wall 62.

24 In a preferred embodiment of corner protector preform 50, the width of inner,
25 vertical spine flap 57 and the height of outer, horizontal spine flap 60 are each equal to a
26 common value which is slightly greater than the thickness of a typical picture frame, e.g., about
27 15/16 inch, for a frame thickness of 7/8 inch. As shown in Figure 7, preform 50 is preferably
28 scored along edge walls 55 and 56 of inner, vertical spine flap 57, and along edge walls 53 and

1 62 of outer, horizontal spine flap 60. These score lines are located along boundaries between
2 adjacent flaps, and facilitate folding the flaps out from the plane of a preform and around a
3 picture frame corner, as will be explained below.

4 Referring again to Figures 2 and 8, corner protector feeder mechanism 70 may
5 be seen to include a longitudinally elongated, rectangularly shaped guide plate 71 having a
6 generally flat upper surface mounted above and parallel to upper surface 34 of work table 32.
7 Guide plate 71 is oriented with its long axis parallel to left and right side walls 72 and 73 of
8 enclosure 31, and protrudes rearwardly beyond rear side wall 74 of the enclosure. As shown
9 in Figures 1, 2, and 8, guide plate 71 of feeder mechanism 70 has through its thickness
10 dimension ~~a perforation~~ an opening 76 having substantially the same outline shape as corner
11 protector preform 50. Guide plate 71 is spaced above upper surface 34 of table 32 by
12 longitudinally disposed support ribs 82, at a distance slightly greater than the thickness of
13 corner protector preform 50, e.g., 5/16 inch for preforms having a thickness of about 1/4 inch.
14 Thus, a corner protector preform 50 placed conformally over ~~perforation~~ opening 76 will drop
15 through the aperture onto work table surface 32, allowing the preform to be slid into operating
16 position under clamping jig 33, as will be described in detail below.

17 As may be seen best by referring to Figure 9, feeder mechanism 70 includes a
18 pusher plate 79 longitudinally slidably mounted in longitudinally disposed guideways consisting
19 of grooves 80 provided in inner facing walls 81 of guide plate support ribs 82. Pusher ~~plate~~
20 plate 79 has a generally uniform thickness, and has a front edge wall 83 in which is formed a
21 groove shaped complementarily to the lower edge wall of preform 50. Preferably, pusher plate
22 79 is made of DELRIN, NYLON, or a similar structural polymer that has good lubricity.

23 As shown in Figure 9, pusher plate 79 has protruding perpendicularly from a rear
24 edge 85 thereof an elongated straight push rod member 84 which protrudes rearwardly of rear
25 vertical wall panel 74 of enclosure 31. Push rod 84 is reciprocally and cyclically actuated
26 longitudinally, i.e., perpendicularly to rear edge 85 of pusher plate 79, in a forward direction to
27 feed a preform 50 forward under clamping jig 33, and rearwardly to retract front edge 83 of the
28 pusher plate into alignment with the rear edge wall of ~~aperture~~ opening 76 through guide plate

1 71, to thereby enable a next preform 50 in a stack to drop through the aperture opening
2 preparatory to its being fed forward for installation on another picture frame corner. In a
3 preferred embodiment, push rod 84 is coupled to the piston of a double acting pneumatic
4 cylinder (not shown) used to cyclically advance and retract pusher plate 79.

5 In a preferred embodiment of apparatus 20, as shown in Figure 1, corner
6 protector installation mechanism 30 includes a plurality of vertically disposed guide rods 77
7 which protrude perpendicularly upwards from upper surface 34 of work table 32. Guide rods
8 77 define between tangents to the outer wall surfaces of inner facing sides of the rods a
9 uniform transverse cross-section, vertically disposed bore 78 which is vertically aligned with
10 guide plate perforation 76 and which is adapted to receive a vertical stack of preforms 50.

11 Referring now to Figures 1, 2 and 8, it may be seen that corner protector
12 installation mechanism 30 includes an adhesive dispensing apparatus 101 for dispersing
13 quantities of adhesive used for bonding corner protectors 50 to picture frames. In a preferred
14 embodiment, adhesive dispensing apparatus 101 includes a hot melt adhesive machine, such
15 as the Autotech Model AT15 Hotmelt Unit, manufactured by the Slautterback Corporation,
16 located at 5 Lower Ragsdale Drive, Monterey, CA 93940-5779. As shown in Figures 1, 2, this
17 embodiment of an adhesive dispensing apparatus includes a machine 102 for melting solid
18 polymer sticks and pumping the molten polymer, and a thermally blanketed, high pressure
19 hose 103 for conveying hot, molten polymer adhesive to an applicator head 104. As shown
20 in Figures 3-6, applicator head 104 has a horizontally elongated body 105 including a generally
21 rectangular block-shaped front portion 106 having a flat, horizontally disposed lower surface
22 107 from which protrude one or preferably two adhesive dispensing nozzles 108. As shown
23 in Figure 2, hot melt adhesive dispensing apparatus 101 includes a pressurized air hose 109
24 and electrical control cable 110 which are interconnected between hot melt pumping machine
25 102 and applicator head 104. Referring to Figure 1, machine 102 includes a melting tank (not
26 shown) located below a hinged lid 111 for receiving and melting sticks of hot melt polymer
27 adhesive, such as H. B. Fuller type HL 9254 hot melt adhesive received into the tank. This
28 type adhesive has a working temperature range of about 270 °F to 325 °F. Machine 102

1 includes an internal heater, and internal control mechanisms which, in response to electrical
2 command signals supplied from an external source, pump molten hot melt adhesive from the
3 melting tank through delivery hose 103 to applicator head 104. Internal control mechanisms
4 within machine 102 also provide electrical signals through control cable 110 to applicator head
5 104 which control flow of pressurized air supplied to the ~~had~~ head through hose 109 which
6 operate to valves within the head, causing jets of pressurized liquid hot melt adhesive to be
7 sprayed from nozzles 108 upon receipt of an external electrical command signal.

8 As may be seen best by referring to Figures 2, 8, and 18, corner protector
9 installation apparatus 20 includes an adjustable support structure 118 for holding and
10 supporting at an adjustable longitudinal distance, or throat depth, applicator head 104 of the
11 apparatus relative to a picture frame held in clamp jig 33.

12 Support structure 118 is mounted on the upper end of a compressor/elevator
13 actuator mechanism 119 which lowers applicator head 104 to force a pair of fingers 141 having
14 flat, co-planar horizontally disposed anvil surfaces 142 which protrude downwards from a front
15 flat anvil portion 120 of head 104 into compressive contact with a corner protector 50 on a
16 picture frame to press flaps of the corner protector preform into bonding contact with semi-
17 liquid hot melt adhesive, upon completion of the adhesive application operation, as will be
18 explained in detail below.

19 As may be seen best by referring to Figures 2, 8, and 18, compressor/elevator
20 actuator 119 of hot melt adhesive dispensing apparatus 101 includes a row of three vertically
21 disposed, laterally spaced apart and aligned support rods 121 fastened at the upper ends
22 thereof to the lower portion of spray gun applicator head support structure 119A. Support
23 rods 121 are vertically slidably supported in sleeve bearings 122 located below an elongated
24 rectangular base plate 123. Base plate 123 is fastened to a structural member 124 within
25 enclosure 31, and is located below a similarly-shaped aperture 125 through work table 32.

26 Referring now to Figures 2 and 8-10 12-17, corner protector installation
27 mechanism 30 may be seen to include a pair of corner flap folder actuators 130L and 130R
28 located on the left and right sides, respectively, of a longitudinal center line of work table 32

1 of the apparatus. As shown in Figure 2, flap folder actuators 130L and 130R are located
2 longitudinally ~~inwards~~ rearwards of clamping jig 33, in a location that places the actuators
3 adjacent to the sides of a frame inserted inwardly under clamp bar 38 of clamping jig 33. Flap
4 folder actuators 130L and 130R are identical in structure and function. Therefore, in the
5 ensuing description, the flap folder actuators will be referred to generally without a subscript.

6
7 As shown in Figures 2 and 8, each flap folder actuator 130, such as left-hand
8 folder actuator 130L, may be seen to include a flat, rectangularly-shaped flap folder arm 131
9 which fits into a complementarily shaped recess 129 provided in upper surface 34 of work table
10 32, flush with the upper surface. Arm 131 is oriented with a long, inner longitudinal edge 132
11 thereof parallel and adjacent to a side of a picture frame protruding diagonally inwardly from
12 beneath clamp bar 38 of clamping jig 33.

13 As may be seen best by referring to Figure 12, each flap holder arm 131 is
14 mounted on the upper transversely disposed horizontal end wall 133 of a vertically disposed,
15 cylindrically-shaped support post 134. Also, corner protector installation mechanism 30
16 includes a linear actuator for elevating support post 134 along its longitudinal axis, to thereby
17 elevate flap folder arm 131 attached to the upper end of the support post upwardly from its rest
18 position ~~recessed in~~ recess 129 in upper surface 34 of work table 31, and a rotary actuator for
19 reciprocally rotating elevator support post 134 about its longitudinal axis, to thereby rotate the
20 flap folder arm ninety degrees away from and back to its rest position, where the linear
21 actuator retracts the flap folder arm into recess 129.

22 Corner protector installation mechanism 30 according to the present invention
23 also includes preferably sensor means which provides a signal indicating that a corner of a
24 picture frame has been fully inserted into clamping jig 33, with the frame moldings adjacent the
25 corner parallel to and proximate inner vertical wall surfaces 238R, 238L of guide plates 36R,
26 36L.

27 Various types of proximity or optical sensors suitable for the foregoing purpose
28 are well known to those skilled in the art. In an example embodiment of apparatus 20 tested

1 by the present inventor, each sensor 170 consisted of a UZJ-111, fixed-focus type micro-photo
2 sensor, manufactured by Matsushita Electric Works, Ltd., Automation Controls Group, 1048
3 Kadoma, Osaka 571, Japan. That sensor contains an infrared light emitting diode and
4 phototransistor arranged within a circuit module with their optical axes generally parallel, and
5 their respective exit and entrance pupils adjacent each other behind an infrared window
6 comprising the outer face of the module. When a surface such as the outer surface of a
7 picture frame molding is positioned within about $5\text{ mm} \pm 2.5\text{ mm}$ of the outer face of the
8 sensor, an output transistor within the sensor is turned on, providing a logic TRUE current
9 through a load resistor connected in series with a collector supply voltage, and the emitter and
10 collector output terminals of the sensor.

11 As shown in Figure 1, a pair of sensors 170R, 170L of the type described above
12 with their outer faces installed in guide plates 36R, 36L, flush with inner surfaces 238R, 238L
13 of guide plates 36R, 36L, respectively, near the inner transverse vertical end walls 171R, 171L
14 thereof, and near upper surface 34 of work table 32. Each sensor 170 produces a logic TRUE
15 signal when a frame molding is parallel to and a predetermined distance from inner surface
16 238R, 238L adjacent the outer face of the sensor. Moreover, apparatus 20 includes an
17 electronic AND circuit 172 for logically ANDING signals from the output terminals of two
18 sensors 170R, 170L of corner protector installation mechanism 30. The output signal from the
19 AND circuit is false when either of the 2 sensors 170R, 170L outputs a false signal, indicating
20 that a picture frame molding near that sensor is not substantially close to and parallel to the
21 sensor. However, when the corner of a frame has been fully inserted into and properly aligned
22 with clamping jig 33 of corner protector installation mechanism 30 of apparatus 20. The logical
23 AND circuit produces a TRUE output signal which initiates a sequence of automatic operations
24 of the corner protector installation mechanism, which are described below. Electronic circuitry
25 for performing the foregoing functions is well known to those skilled in the art, and therefore
26 need not be described in further detail here. For example, such circuitry can be implemented
27 in a Programmable Logic Controller, PLC 433 135, as shown in Figure 2, or a general purpose
28 microprocessor or micro controller.

OPERATION OF THE INVENTION

In response to a TRUE output signal from AND circuit 472 when both sensors 170L, 170R produce TRUE output signals, Programmable Logic Controller (PLC) 433 135 issues in sequence drive signals to the various actuators of corner protector installer mechanism 30 of apparatus 20 according to the present invention, as follows:

1. Vertical stacks of corner protector preforms 50 are loaded into bores 78 between guide rods 77 of feeder mechanisms 70 of installer mechanism 30. (Figures 1 and 8)

2. Power is turned on and PLC 433 135 resets and checks mechanism 30 of apparatus 20, readying the PLC for outputting sequential drive signal commands to the various actuators of the apparatus. A program for the operational sequence of apparatus 20 is stored in electronic memory means in PLC 433 135. This program can be executed via an internal or external computer. (Figure 2)

3. Actuator cylinder 92 of feeder mechanism 70 in installer mechanism 30 is actuated to reciprocate piston rod 94, thereby moving an individual corrugated corner protector blank preform 50 forward into position below clamp bar 38 of the installer mechanism. (Figure 9)

4. A first corner C1 of a picture frame A having left and right channel moldings D and B is inserted into position beneath clamp bars 38 and over blank 50 of installer mechanism 30. (Figure 10)

5. Frame A is positioned relative to apparatus 20 so that corner C1 of the frame is fully inserted into clamping jig 33 of mechanism 30. (Figure 10)

6. Sensors 170L, 170R of installer mechanism 30 output TRUE signals, causing AND circuit 472 to output a TRUE signal, in turn causing PLC 423 135 to simultaneously issue drive signals to the installer mechanism, as follows: (Figure 10)

7. Hold down clamp bar 38 of clamping jig 33 of mechanism 30 is forced downward onto the adjacent molding channels D and B of frame A which intersect at corner C1. (Figure 10)

1 8. Hot melt adhesive machine 102 is then actuated, causing applicator head 104
2 to spray blobs E of semi-liquid hot melt adhesive onto the upper surface of ~~left~~ right-hand
3 frame molding ~~Θ B~~. (Figure 11)

4 9. Blank preform 50 under corner C1 of frame A is automatically manipulated as
5 follows: First, rectangular outer spine flap 60 and securement flap 61 of preform 50 are bent
6 upwardly in unison into a vertically disposed orientation by elevating right-hand flap folder arm
7 131R of mechanism 30 from its recess 129R, with the flap folder arm in its clockwise position.
8 (Figure 12)

9 10. Securement flap 61 of preform 50 is bent inwardly and downwardly over ~~left~~ right
10 frame channel ~~Θ B~~ by rotating right-hand flap folder arm 131R counterclockwise. (Figure 13)

11 11. Hot melt adhesive applicator head 104 is again actuated to spray blobs F of
12 semi-liquid adhesive onto the upper surface of securement flap 61. (Figure 14)

13 12. ~~Right-hand~~, Upper triangular cover flap 52 and inner spine flap 57 of preform 50
14 are bent as a unit into a vertically disposed orientation by extending ~~right~~ left-hand flap folder
15 arm ~~462R~~ 131L upwardly from recess 129R L. (Figure 15)

16 13. Upper cover flap 52 of preform 50 is bent inwardly and downwardly over ~~right~~ left-
17 hand frame channel ~~B D~~ by rotating flap folder arm ~~452L~~ 131L ninety degrees clockwise.
18 (Figure 16)

19 14. Right flap folder arm 131R is rotated ninety degrees clockwise to its angular rest
20 position, and retracted downwardly into recess 129R to its vertical rest position. (Figures 16,
21 17)

22 15. Hot melt adhesive applicator head gun 104 of mechanism 30 is lowered toward
23 frame A, pressing fingers 141 protruding downwardly from front flat anvil portion 120 of the
24 head, located forward of nozzles 108, down against upper cover flap 52, thereby pressing the
25 flap down into blobs of adhesive between it and securement flap 61. (Figures 17, 18, 19)

26 16. Left flap folder arm 131L of mechanism 30 is rotated ninety degrees
27 counterclockwise to its angular rest position. (Figure ~~2~~ 15)

1 17. Left flap folder arm 131L of mechanism 30 is retracted downwardly into recess
2 129L to its vertical rest position. (Figure 2)

3 18. Hold down clamp bar 38 of clamping jig 33 of mechanism 30 is retracted vertically
4 upwards to its rest position, unclamping corner C1 of frame A. (Figure 9)

5 19. Frame A is retracted from apparatus 20, disengaging corner C1 from clamping
6 jig 33.

7 20. Frame A is rotated ninety degrees in a horizontal plane, and steps 4-18 repeated
8 to attach a corner protector 50 to a second corner C2 of frame A.

9 21. Step 20 is repeated for the remaining two corners C3, C4 of frame A.